

上海墨鑫泵阀有限公司

ISW、ISWH、ISWB、IHWB 单级单吸卧式离心泵完整选型参数

型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
15-80	15	1.1	0.3	8.5	26	2800	0.18	2.3
		1.5	0.42	8	34			
		2.0	0.55	7	34			
20-110	20	1.8	0.5	16	25	2800	0.37	2.3
		2.5	0.69	15	34			
		3.3	0.91	13.5	35			
20-160	20	1.8	0.5	33	19	2900	0.75	2.3
		2.5	0.69	32	25			
		3.3	0.91	30	23			
25-110	25	2.8	0.78	16	34	2900	0.55	2.3
		4	1.11	15	42			
		5.2	1.44	13.5	41			
25-125	25	2.8	0.78	20.6	28	2900	0.75	2.3
		4	1.11	20	36			
		5.2	1.44	18	35			
25-125A	25	2.5	0.69	17	35	2900	0.55	2.3
		3.6	1.0	16				
		4.6	1.28	14.4				
25-160	25	2.8	0.78	33	24	2900	1.5	2.3
		4	1.11	32	32			
		5.2	1.44	30	33			
25-160A	25	2.6	0.12	29	31	2900	1.1	2.3
		3.7	1.03	28				
		4.9	1.36	26				
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
32-100(I)	32	4.4	1.22	13.2	48	2900	0.75	2.0
		6.3	1.75	12.5	54			
		8.3	2.32	11.3	53			

32-125	32	3.5 5 6.5	0.97 0.39 1.8	22 20 18	40 44 42	2900	0.75	2.3
32-125A	32	3.1 4.5 5.8	0.86 1.25 1.61	17.6 16 14.4	43	2900	0.55	2.3
32-160(l)	32	4.4 6.3 8.3	1.22 1.75 2.32	33.2 32 30.2	34 40 42	2900	2.2	2.0
32-200(l)	32	4.4 6.3 8.3	1.22 1.75 2.32	50.5 50 48	26 33 35	2900	4	2.0
32-200A	32	2.8 4 5.2	0.78 1.11 1.44	44.6 44 42.7	34 40 42	2900	2.2	2.0
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
40-100	40	4.4 6.3 8.3	1.22 1.75 2.31	13.2 12.5 11.3	48 54 53	2900	0.55	2.3
40-100A	40	3.9 5.6 7.4	1.08 1.56 2.06	10.6 10 9	52	2900	0.37	2.3
40-125	40	4.4 6.3 8.3	1.22 1.75 2.31	21 20 18	41 46 43	2900	1.1	2.3
40-125A	40	3.9 5.6 7.4	1.08 1.56 2.06	17.6 16 14.4	40 45 41	2900	0.75	2.3
40-160	40	4.4 6.3 8.3	1.22 1.75 2.31	33 32 30	35 40 40	2900	2.2	2.3
40-160A	40	4.1 5.9 7.8	1.14 1.64 2.17	29 28 26.3	34 39 39	2900	1.5	2.3

40-160B	40	3.8 5.5 7.2	1.06 1.53 2.0	25.5 24 22.5	34 38 37	2900	1.1	2.3
40-200	40	4.4 6.3 8.3	1.22 1.75 2.31	51 50 48	26 33 32	2900	4	2.3
40-200A	40	4.1 5.9 7.8	1.14 1.64 2.17	45 44 42	26 31 30	2900	3	2.3
40-200B	40	3.7 5.3 7.0	1.03 1.47 1.94	38 36 34.5	29	2900	2.2	2.3
40-250	40	4.4 6.3 8.3	1.22 1.75 2.31	82 80 74	24 28 28	2900	7.5	2.3
40-250A	40	4.1 5.9 7.8	1.14 1.64 2.17	72 70 65	24 28 27	2900	5.5	2.3
40-250B	40	3.8 5.5 7.0	1.06 1.53 1.94	61.5 60 56	23 27 26	2900	4	2.3
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
40-100(I)	40	8.8 12.5 16.3	2.44 3.47 4.53	13.2 12.5 11.3	55 62 60	2900	1.1	2.3
40-100(I)A	40	8 11 14.5	2.22 3.05 4.03	10.6 10 9	60	2900	0.75	2.3
40-125(I)	40	8.8 12.5 16.3	2.44 3.47 4.53	21.2 20 17.8	49 58 57	2900	1.5	2.3
40-125(I)A	40	8 11 14.5	2.22 3.05 4.03	17 16 14	57	2900	1.1	2.3

40-160(I)	40	8.8 12.5 16.3	2.44 3.47 4.53	33 32 30	45 52 51	2900	3	2.3
40-160(I)A	40	8.2 11.7 15.2	2.28 3.25 4.22	29 28 26	44 51 50	2900	2.2	2.3
40-160(I)B	40	7.3 10.4 13.5	2.38 2.89 3.75	23 22 20.5	50	2900	1.5	2.3
40-200(I)	40	8.8 12.5 16.3	2.44 3.47 4.53	51.2 50 48	38 46 46	2900	5.5	2.3
40-200(I)A	40	8.3 11.7 15.3	2.31 3.25 4.25	45.0 44 42	37 45 45	2900	4	2.3
40-200(I)B	40	7.5 10.6 13.8	2.08 2.94 3.83	37 36 34	44	2900	3	2.3
40-250(I)	40	8.8 12.5 16.3	2.44 3.47 4.53	81.2 80 77.5	31 38 40	2900	11	2.3
40-250(I)A	40	8.2 11.6 15.2	2.28 3.22 4.22	71.0 70 68	38	2900	7.5	2.3
40-250(I)B	40	7.6 10.8 14	2.11 3.0 3.89	61.4 60 58	37	2900	7.5	2.3
40-250(I)C	40	7.1 10.0 13.1	1.97 2.78 3.64	53.2 52 50.4	36	2900	5.5	2.3
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m ³ /h	L/S	m	%	r/min	KW	(NPSH) r
50-100	50	8.8 12.5 16.3	2.44 3.47 4.53	13.6 12.5 11.3	55 62 60	2900	1.1	2.3

50-100A	50	8 11 14.5	2.22 3.05 4.03	11 10 9	60	2900	0.75	2.3
50-125	50	8.8 12.5 16.3	2.44 3.47 4.53	21.5 20 17.8	49 58 57	2900	1.5	2.3
50-125A	50	8 11 14.5	2.22 3.05 4.03	17 16 14	57	2900	1.1	2.3
50-160	50	8.8 12.5 16.3	2.44 3.47 4.53	33 32 30	45 52 51	2900	3	2.3
50-160A	50	8.2 11.7 15.2	2.28 3.25 4.22	29 28 26	44 51 50	2900	2.2	2.3
50-160B	50	7.3 10.4 13.5	2.38 2.89 3.75	23 22 20.5	50	2900	1.5	2.3
50-200	50	8.8 12.5 16.3	2.44 3.47 4.53	52 50 48	38 46 46	2900	5.5	2.3
50-200A	50	8.3 11.7 15.3	2.31 3.25 4.25	45.8 44 42	37 45 45	2900	4	2.3
50-200B	50	7.5 10.6 13.8	2.08 2.94 3.83	37 36 34	44	2900	3	2.3
50-250	50	8.8 12.5 16.3	2.44 3.47 4.53	82 80 77.5	29 38 40	2900	11	2.3
50-250A	50	8.2 11.6 15.2	2.28 3.22 4.22	71.5 70 68	38	2900	7.5	2.3
50-250B	50	7.6 10.8 14	2.11 3.0 3.89	61.4 60 58	37	2900	7.5	2.3

50-250C	50	7.1 10.0 13.1	1.97 2.78 3.64	53.2 52 50.4	36	2900	5.5	2.3
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
50-100(I)	50	17.5 25 32.5	4.86 6.94 9.03	13.7 12.5 10.5	67 69 69	2900	1.5	2.5
50-100(I)A	50	15.6 22.3 29	4.3 6.19 8.1	11 10 8.4	65 67 68	2900	1.1	2.5
50-125(I)	50	17.5 25 32.5	4.86 6.94 9.03	21.5 20 18	60 68 67	2900	3	2.5
50-125(I)A	50	15.6 22.3 29	4.33 6.19 8.1	17 16 13.6	58 66 65	2900	2.2	2.5
50-160(I)	50	17.5 25 32.5	4.68 6.94 9.03	34.4 32 27.5	54 63 60	2900	4	2.5
50-160(I)A	50	16.4 23.4 30.4	4.56 6.5 8.44	30 28 24	54 62 59	2900	4	2.5
50-160(I)B	50	15.0 21.6 28	4.17 6.0 7.78	26 24 20.6	58	2900	3	2.5
50-200(I)	50	17.5 25 32.5	4.86 6.94 9.03	52.7 50 45.5	49 58 59	2900	7.5	2.5
50-200(I)A	50	16.4 23.5 30.5	4.56 6.53 8.47	46.4 44 40	48 57 58	2900	7.5	2.5
50-200(I)B	50	15.2 21.8 28.3	4.22 6.06 7.86	40 38 34.5	55	2900	5.5	2.5

50-250(I)	50	17.5 25 32.5	4.86 6.94 9.03	82 80 76.5	39 50 52	2900	15	2.5
50-250(I)A	50	16.4 23.4 30.5	4.56 6.5 8.47	71.5 70 67	39 50 52	2900	11	2.5
50-250(I)B	50	15 21.6 28	4.17 6.0 7.78	61 60 57.4	38 49 54	2900	11	2.5
50-315(I)	50	17.5 25 32.5	4.86 6.94 9.03	128 125 122	30 40 44	2900	30	2.5
50-315(I)A	50	16.6 23.7 31	4.61 6.58 8.6	115 113 110	30 40 44	2900	22	2.5
50-315(I)B	50	15.7 22.5 29.2	4.36 6.25 8.0	103 101 98	39	2900	18.5	2.5
50-315(I)C	50	14.4 20.6 26.8	4.0 5.72 7.44	86 85 83	38	2900	15	2.5
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
		m3/h	L/S	m	%	r/min	KW	(NPSH) r
65-100	65	17.5 25 32.5	4.86 6.94 9.03	13.7 12.5 10.5	67 69 69	2900	1.5	2.5
65-100A	65	15.6 22.3 29	4.3 6.19 8.1	11 10 8.4	65 67 68	2900	1.1	2.5
65-125	65	17.5 25 32.5	4.86 6.94 9.03	21.5 20 18	60 68 67	2900	3	2.5
65-125A	65	15.6 22.3 29	4.33 6.19 8.1	17 16 14.4	58 66 65	2900	2.2	2.5

65-160	65	17.5 25 32.5	4.86 6.94 9.03	34.4 32 27.5	54 63 60	2900	4	2.5
65-160A	65	16.4 23.4 30.4	4.56 6.5 8.44	30 28 24	54 62 59	2900	4	2.5
65-160B	65	15.0 21.6 28	4.17 6.0 7.78	26 24 20.6	58	2900	3	2.5
65-200	65	17.5 25 32.5	4.86 6.94 9.03	52.7 50 45.5	49 58 59	2900	7.5	2.5
65-200A	65	16.4 23.5 30.5	4.56 6.53 8.47	46.4 44 40	48 57 58	2900	7.5	2.5
65-200B	65	15.2 21.8 28.3	4.22 6.06 7.86	40 38 34.5	55	2900	5.5	2.5
65-250	65	17.5 25 32.5	4.86 6.94 9.03	82 80 76.5	39 50 52	2900	15	2.5
65-250A	65	16.4 23.4 30.5	4.56 6.5 8.47	71.5 70 67	39 50 52	2900	11	2.5
65-250B	65	15 21.6 28	4.17 6.0 7.78	61 60 57.4	38 49 54	2900	11	2.5
65-315	65	17.5 25 32.5	4.86 6.94 9.03	127 125 122	32 40 44	2900	30	2.5
65-315A	65	16.6 23.7 31	4.61 6.58 8.6	115 113 110	32 40 44	2900	22	2.5
65-315B	65	15.7 22.5 29.2	4.36 6.25 8.0	103 101 98	39	2900	18.5	2.5

65-315C	65	14.4 20.6 26.8	4.0 5.72 7.44	86 85 83	38	2900	15	2.5
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
65-100(I)	65	35	9.72	13.8	67	2900	3	3.0
		50	13.9	12.5	73			
		65	18.1	10	70			
65-100(I)A	65	31.3	8.7	11	66	2900	2.2	3.0
		44.7	12.4	10	72			
		58	16.1	8	69			
65-125(I)	65	35	9.72	22	67	2900	5.5	3.0
		50	13.9	20	72.5			
		65	18.1	17	70			
65-125(I)A	65	31.3	8.7	17.5	66	2900	4	3.0
		44.7	12.5	16	71			
		58	16.1	13.6	69			
65-160(I)	65	35	9.72	35	63	2900	7.5	3.0
		50	13.9	32	71			
		65	18.1	28	70			
65-160(I)A	65	32.7	9.1	30.6	62	2900	7.5	3.0
		46.7	13.0	28	70			
		61	16.9	24	69			
65-160(I)B	65	30.3	8.4	26		2900	5.5	3.0
		43.3	12.0	24	69			
		56.3	15.6	21				
65-200(I)	65	35	9.72	53.5	55	2900	15	3.0
		50	13.9	50	67			
		65	18.1	46	68			
65-200(I)A	65	32.8	9.1	47	54	2900	11	3.0
		47	13.1	44	66			
		61	16.9	40	67			
65-200(I)B	65	30.5	8.5	40.6		2900	7.5	3.0
		43.5	12.1	38	65			
		56.6	15.7	33.4				

65-250(I)	65	35 50 65	9.72 13.9 18.1	83 80 72	52 59 60	2900	22	3.0
65-250(I)A	65	32.5 46.7 61	9.0 13.0 16.9	73 70 63	52 59 60	2900	18.5	3.0
65-250(I)B	65	30 43.3 56	8.3 12.0 15.6	62 60 54	58	2900	15	3.0
65-315(I)	65	35 50 65	9.72 13.9 18.1	128 125 121	44 54 57	2900	37	3.0
65-315(I)A	65	32.5 46.5 60.5	9.0 12.9 16.8	112.6 110 106.4	43 54 57	2900	30	3.0
65-315(I)B	65	31 44.5 58	8.6 12.4 16.1	102.5 100 98	53	2900	30	3.0
65-315(I)C	65	29 41 53.6	8.1 11.4 14.9	87 85 83	51	2900	22	3.0
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
80-100	80	35 50 65	9.72 13.9 18.1	13.8 12.5 10	67 73 70	2900	3	3.0
80-100A	80	31.3 44.7 58	8.7 12.5 16.1	11 10 8	66 72 69	2900	2.2	3.0
80-125	80	35 50 65	9.72 13.9 18.1	22 20 17	67 72.5 70	2900	5.5	3.0
80-125A	80	31.3 45 58	8.7 12.5 16.1	17.5 16 13.6	66 71 69	2900	4	3.0

80-160	80	35 50 65	9.72 13.9 18.1	35 32 28	63 71 70	2900	7.5	3.0
80-160A	80	32.7 46.7 61	9.1 13.0 16.9	30.6 28 24	62 70 69	2900	7.5	3.0
80-160B	80	30.3 43.3 56.3	8.4 12.0 15.6	26 24 21	69	2900	5.5	3.0
80-200	80	35 50 65	9.72 13.9 18.1	53.5 50 46	55 67 68	2900	15	3.0
80-200A	80	32.8 47 61	9.1 13.1 16.9	47 44 40	54 66 67	2900	11	3.0
80-200B	80	30.5 43.5 56.6	8.5 12.1 15.7	40.6 38 33.4	65	2900	7.5	3.0
80-250	80	35 50 65	9.72 13.9 18.1	83 80 72	52 59 60	2900	22	3.0
80-250A	80	32.5 46.7 61	9.0 13.0 16.9	73 70 63	52 59 60	2900	18.5	3.0
80-250B	80	30 43.3 56	8.3 12.0 15.6	62 60 54	58	2900	15	3.0
80-315	80	35 50 65	9.72 13.9 18.1	128 125 122	43 54 57	2900	37	3.0
80-315A	80	32.5 46.5 60.5	9.0 12.9 16.8	112.6 110 107.4	43 54 57	2900	30	3.0
80-315B	80	31 44.5 58	8.6 12.4 16.1	102.5 100 98	53	2900	30	3.0

80-315C	80	29 41 53.6	8.1 11.4 14.9	98 85 83	51	2900	22	3.0
80-350	80	35 50 65	9.72 13.9 18.1	146 150 142	55 66 67	2900	55	3.0
80-350A	80	31 44.5 58	8.6 12.4 16.1	138.4 142 134.8	65	2900	45	3.0
80-350B	80	29 41 53.6	8.1 11.4 14.9	131.4 135 127.8	63	2900	37	3.0
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
80-100(I)	80	70 100 130	19.4 27.8 36.1	13.6 12.5 11	66 76 75	2900	5.5	4.5
80-100(I)A	80	62.6 89 116	17.4 24.7 32.2	11 10 8.8	64 74 74	2900	4	4.5
80-125(I)	80	70 100 130	19.4 27.8 36.1	23.5 20 14	70 76 65	2900	11	4.5
80-125(I)A	80	62.6 89 116	17.4 24.7 32.2	19 16 11	68 74 65	2900	7.5	4.5
80-160(I)	80	70 100 130	19.4 27.8 36.1	36.5 32 24	70 76 65	2900	15	4.5
80-160(I)A	80	65.4 93.5 121.6	18.2 26.0 33.8	32 28 21	68 74 67	2900	11	4.5
80-160(I)B	80	60.6 86.6 112.5	16.8 24.1 31.3	72 24 18	72	2900	11	4.5

80-200(I)	80	70 100 130	19.4 27.8 36.1	54 50 42	65 74 73	2900	22	4.0
80-200(I)A	80	65.4 93.5 121.6	18.2 26.0 33.8	47.5 44 37	64 73 72	2900	18.5	4.0
80-200(I)B	80	61 87 113	16.9 24.2 31.4	41 38 32	71	2900	15	4.0
80-250(I)	80	70 100 130	19.4 27.8 36.1	87 80 68	62 69 68	2900	37	4.0
80-250(I)A	80	65.4 93.5 121.6	18.2 26.0 33.8	76 70 59.5	61 68 67	2900	30	4.0
80-250(I)B	80	61 87 113	16.9 24.2 31.4	65 60 51	66	2900	30	4.0
80-315(I)	80	70 100 130	19.4 27.8 36.1	132 125 114	55 66 67	2900	75	4.0
80-315(I)A	80	66.5 95 123.6	18.5 26.4 34.3	119 113 103	55 66 67	2900	55	4.0
80-315(I)B	80	63 90 117	17.5 25 32.5	106.6 101 92	65	2900	45	4.0
80-315(I)C	80	58 82 107	16.1 22.8 29.7	90 85 76	63	2900	37	4.0
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
100-100	100	70 100 130	19.4 27.8 36.1	13.6 12.5 11	66 76 75	2900	5.5	4.5

100-100A	100	62.6 89 116	17.4 47 32.2	11 10 8.8	64 74 74	2900	4	4.5
100-125	100	70 100 130	19.4 27.8 36.1	23.5 20 14	70 76 65	2900	11	4.5
100-125A	100	62.6 89 116	17.4 24.7 32.2	19 16 11	68 74 63	2900	7.5	4.5
100-160	100	70 100 130	19.4 27.8 36.1	36.5 32 24	70 76 65	2900	15	4.5
100-160A	100	65.4 93.5 121.6	18.2 26.0 33.8	32 28 21	68 74 67	2900	11	4.5
100-160B	100	60.6 86.6 112.5	16.8 24.1 31.3	27 24 18	72	2900	11	4.5
100-200	100	70 100 130	19.4 27.8 36.1	54 50 42	65 74 73	2900	22	4.0
100-200A	100	65.4 93.5 121.6	18.2 26.0 33.8	47.5 44 37	64 73 72	2900	18.5	4.0
100-200B	100	61 87 113	16.9 24.2 31.4	41 38 32	71	2900	15	4.0
100-250	100	70 100 130	19.4 27.8 36.1	37 80 68	62 69 68	2900	37	4.0
100-250A	100	65.4 93.5 121.6	18.2 26.0 33.8	76 70 59.5	61 68 67	2900	30	4.0
100-250B	100	61 87 113	16.9 24.2 31.4	65 60 51	66	2900	30	4.0

100-315	100	70 100 130	19.4 27.8 36.1	132 125 114	55 66 67	2900	75	4.0
100-315A	100	66.5 95 123.6	18.5 26.4 34.3	119 113 103	65 66 67	2900	55	4.0
100-315B	100	63 90 117	17.5 25 32.5	106.6 101 92	65	2900	45	4.0
100-315C	100	58 82 107	16.1 22.8 29.7	90 85 76	63	2900	37	4.0
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
100-100(I)	100	96 160 192	26.7 44.4 53.3	14 12.5 10	64 73 70	2900	11	4.5
100-125(I)	100	96 160 192	26.7 44.4 53.3	24 20 14	62 74 69	2900	15	4.5
100-125(I)A	100	84 140 168	23.3 39 46.7	20 17 12	64 72 68	2900	11	4.5
100-160(I)	100	96 160 192	26.7 44.4 53.3	36 32 27	69 79 75	2900	22	5.6
100-160(I)A	100	84 140 168	23.3 39 46.7	32 28 23.5	66 76 72	2900	18.5	5.0
100-200(I)	100	96 160 192	26.7 44.4 53.3	53 50 45	69 79 78	2900	37	5.2
100-200(I)A	100	84 140 168	23.3 39 46.7	48 45 40	64 74 73	2900	30	4.5

100-200(I)B	100	60 100 120	16.7 27.8 33.3	43 40 36	72	2900	22	4.5
100-250(I)	100	96 160 192	26.7 44.4 53.3	83 80 72	65 77 74	2900	55	4.8
100-250(I)A	100	84 140 168	23.3 39 46.7	75 72 65	60 72 69	2900	45	4.5
100-250(I)B	100	60 100 120	16.7 27.8 33.3	68 65 58	70	2900	37	4.5
100-350	100	60 100 120	16.7 27.8 33.3	153.6 150 142	72 57 74	2900	90	4.0
100-350A	100	61 87 113	16.9 24.2 31.4	145.6 142 134	75	2900	75	4.0
100-350B	100	58 82 107	16.1 22.8 29.7	138.6 135 127	75	2900	55	4.0
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
125-100	125	96 160 192	26.7 44.4 53.3	13 12.5 12	82	2900	11	4.0
125-100A	125	86 143 172	23.9 39.7 47.8	10.4 10 9.6	77	2900	7.5	4.0
125-125	125	96 160 192	26.7 44.4 53.3	22.6 20 17	80	2900	15	4.0
125-125A	125	86 143 172	23.9 39.7 47.8	18 16 13.6	77	2900	11	4.0

125-160	125	96 160 192	26.7 44.4 53.3	36 32 28	78	2900	22	4.0
125-160A	125	90 150 180	25 41.7 50	31.5 28 24.5	76	2900	18.5	4.0
125-160B	125	83 138 166	21.7 38.3 46.1	27 24 21	73	2900	15	4.0
125-200	125	96 160 192	26.7 44.4 53.3	55 50 46	77	2900	37	5.5
125-200A	125	90 150 180	25 41.7 50	48.4 44 40.5	76	2900	30	5.5
125-200B	125	83 138 166	21.7 38.3 46.1	41.3 37.5 34.5	75	2900	22	5.5
125-250	125	96 160 192	26.7 44.4 53.3	87 80 73	75	2900	55	5.0
125-250A	125	90 150 180	25 41.7 50	76 70 84	74	2900	45	5.5
125-250B	125	83 138 166	21.7 38.3 46.1	65 60 55	73	2900	37	5.5
125-315	125	96 160 192	26.7 44.7 53.3	133 125 119	70	2900	90	5.0
125-315A	125	90 150 180	25 41.7 50	117 110 104.6	70	2900	75	5.0
125-315B	125	86 143 172	23.9 39.7 47.8	106.4 100 95.2	69	2900	75	5.0

125-315C	125	80.5 134 161	22.4 37.2 44.7	96 88 86	67	2900	55	5.0
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
150-125	150	96 160 192	26.7 44.4 53.3	22.6 24 17	66 76 76	2900	11	4.0
150-125A	150	90 150 180	25 41.7 50	18 16 13.6	77	2900	7.5	4.0
150-160	150	96 160 192	26.7 44.4 53.3	36 32 27	75	2900	22	4.0
150-160A	150	90 150 180	25 41.7 50	32 28 23.5	76	2900	18.5	4.0
150-160B	150	84 140 168	23.3 39 46.7	27 24 21	73	2900	15	4.0
150-200	150	140 200 260	38.9 55.6 72.2	13.8 12.5 10.6	68 78 78	1450	15	3.0
150-200A	150	125 176 232.5	34.7 49.7 64.6	11 10 8.5	66 76 76	1450	11	3.0
150-200B	150	84 140 168	23.3 39 46.7	41 38 34	75	2900	22	4.0
150-250	150	140 200 260	38.9 55.6 72.2	21.8 20 17	73 79 77	1450	18.5	3.0
150-250A	150	129 184.4 240	35.8 51.2 66.7	18.5 17 14.4	72 78 76	1450	15	3.0

150-250B	150	117 167 217.5	32.5 46.4 60.4	15.2 14 12	76	1450	11	3.0
150-315	150	140 200 260	38.9 55.6 72.2	33.8 32 28	70 78 73	1450	30	2.5
150-315A	150	131 187 243	36.4 51.9 67.5	29.5 28 24.5	69 77 77	1450	22	3.5
150-315B	150	121 173 225	33.5 48.1 62.5	25 24 21	76	1450	18.5	3.5
150-350	150	96 160 192	26.7 44.4 53.3	153.6 150 142.8	80	2900	110	5.5
150-350A	150	90 150 180	25 41.7 50	145.6 142 134.8	70	2900	90	5.2
150-350B	150	84 140 168	23.3 39 46.7	138.6 135 127.8	65 76 74	2900	75	5.5
150-400	150	140 200 260	38.9 55.6 72.2	53 50 44	68 75 71	1450	45	3.5
150-400A	150	131 187 243	36.4 51.9 67.5	46.6 44 38.3	67 74 70	1450	37	3.5
150-400B	150	122 174 226.5	33.9 48.3 62.9	40 38 33	73	1450	30	3.5
150-400C	150	112 160 208	31.1 44.4 57.8	34 32 28	71	1450	22	3.5
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r

150-250(I)	150	120 200 240	33.3 55.6 66.7	87 80 72	65 76 74	2900	75	4.5
150-250(I)A	150	112 187 224	31.1 51.9 62.2	76 70 63	64 75 73	2900	55	4.5
150-250(I)B	150	104 173 208	28.9 48.1 57.8	65 60 54	63 74 72	2900	45	4.5
150-315(I)	150	120 200 240	33.3 55.6 66.7	133 125 120	58 73 75	2900	110	4.5
150-315(I)A	150	112 187 224	31.1 51.9 62.2	116 110 105	57 72 74	2900	90	4.5
150-315(I)B	150	104 173 208	28.9 48.1 57.8	100 95 91	55 70 72	2900	75	4.5
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
200-200	200	140 200 260	38.9 55.6 72.2	13.8 12.5 10.6	68 78 78	1450	15	3.0
200-200A	200	125 179 232.5	34.7 49.7 64.6	11 10 8.5	66 76 76	1450	11	3.0
200-250	200	140 200 260	21.8 20 17	21.8 20 17	73 79 77	1450	18.5	3.0
200-250A	200	129 184.4 240	18.5 17 14.4	18.5 17 14.4	72 78 76	1450	15	3.0
200-250B	200	117 167 217.5	15.2 14 12	15.2 14 12	76	1450	11	3.0

200-315	200	140 200 260	33.8 32 28	33.8 32 28	70 78 78	1450	30	3.5
200-315A	200	131 189 243	29.5 28 24.5	29.5 28 24.5	69 77 77	1450	22	3.5
200-315B	200	121 173 225	25 24 21	25 24 21	76	1450	18.5	3.5
200-400	200	140 200 260	53 50 44	53 50 44	68 75 71	1450	45	3.5
200-400A	200	131 187 243	46.6 44 38.3	46.6 44 38.3	67 74 70	1450	37	3.5
200-400B	200	122 174 226.5	40 38 33	40 38 33	73	1450	30	3.5
200-400C	200	112 160 208	34 32 28	34 32 28	71	1450	22	3.5
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
200-200(I)	200	280 400 520	77.8 111.1 144	13.4 12.5 10.5	70 80 79	1450	22	4.0
200-200(I)A	200	250 358 465	69.4 90.4 129.2	10.7 10 8.5	68 73 77	1450	18.5	4.0
200-250(I)	200	280 400 520	77.8 111.1 144	22.2 20 14	75 80 72	1450	30	4.0
200-250(I)A	200	250 358 465	69.4 99.4 129.2	18 16 11.2	73 78 70	1450	22	4.0

200-250(I)B	200	226 322 419	62.8 89.4 116.4	14.4 13 7.3	70 75 67	1450	18.5	4.0
200-315(I)	200	280 400 520	77.8 111.4 144	36 32 26	73 80 75	1450	55	4.0
200-315(I)A	200	262 374 486	72.8 103.9 135	31.5 28 23	72 79 74	1450	45	4.0
200-315(I)B	200	242 346 450	67.3 96.1 125	27 24 19.5	78	1450	37	4.0
200-400(I)	200	280 400 520	77.8 111.4 144	54.5 50 39	75 81 77	1450	75	4.0
200-400(I)A	200	262 374 486	72.8 103.9 135	48 44 34	80	1450	75	4.0
200-400(I)B	200	242 346 450	67.2 96.1 125	41.4 38 29.6	78	1450	55	5.0
200-400(I)C	200	224 320 416	62.2 88.9 115.6	34.9 32 25	76	1450	45	5.0
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
250-250	250	350 550 650	97.2 152.8 180.5	22 20 16	78 82 81	1450	45	5.0
250-250A	250	300 500 600	83.3 139 166.7	18.3 17 14	76 80 80	1450	37	5.0
250-235	250	300 500 600	83.3 139 166.7	14 12.5 11	73 78 70	1480	22	4.5

250-300	250	300 500 600	83.3 139 166.7	22 20 16	78	1480	37	4.5
250-315	250	350 550 650	97.2 152.8 180.5	34 32 28	76 80 79	1450	75	5.5
250-315A	250	300 500 600	83.3 139 166.7	29.5 28 24	74 78 77	1450	55	5.5
250-315B	250	260 450 520	72.2 125 144.4	25 24 20	70 74 72	1450	45	5.5
250-400	250	300 500 600	83.3 139 166.7	54.5 50 39	72	1480	90	4.5
型号	口径	流量		扬程	效率	转速	电机功率	必需汽蚀余量
	mm	m3/h	L/S	m	%	r/min	KW	(NPSH) r
300-235	300	480 720 900	133.3 200 250	20 18 15.5	77 81 74	970	55	5.0
300-235A	300	438 607 821	121.7 182.5 228.1	16.5 15 13	75 79 72	970	45	5.0
300-235B	300	400 600 750	111.1 167.0 208.3	14 12.5 11	73 77 70	970	37	5.0
300-300	300	480 720 900	133.3 200 250	31 28 25	77 81 77	970	75	5.0
300-300A	300	444 666 833	123.3 185 231.4	26.5 24 21.5	76 80 76	970	75	5.0
300-300B	300	415 623 779	115.3 173.1 261.4	23 21 18.5	79	970	55	5.0

300-380	300	480 720 900	133.3 200 250	48 44 34	84	970	132	5.0
300-380A	300	444 666 833	123.3 185 231.4	41.4 38 30	80	970	110	5.0
300-380B	300	409 614 767	113.6 170.6 213.1	35 32 25	78	970	90	5.0
300-235(I)	300	718 1080 1345	199.4 300 373.6	44.6 40 34.6	82	1450	160	5.5